



1	2	3	4	5	6	7	8	9	10
CS2	CS1	VSS	VDD	VO	RS	RW	E	DB0	DB1
DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK	VOUT	RST

SPECIFICATION:

- 1). Driving: Duty:1/64, Bias:1/9, Vdd:5.0V, Vlcd:7.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Y-G
- 4). Operating temp.: -20°C~+70°C
- 5). Storage temp.: -30°C~+80°C
- 6). Control IC: S6B0107,AIP31107
- 7). BACKLIGHT: Y-G
- 8). DIMENSIONS WITH MARK "" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

TCC 深圳市三元晶科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. SYB19264A2V31-639M1N7R-B5NGV1 GENERAL TOL: ±0.2

APPROVED BY CHECKED BY DRAWING BY PAGE: 1 OF 1 UNIT: mm

Luoxian 2015/04/1 PROJECTION

DATE

REVISION RECORD

REV

A

B

C

D