



- Specification:
- 1). Driving: Duty: 1/64, Bias: 1/9, VLCD: 9.0V(Ref), VDD: 3.3V
 - 2). Viewing Direction: 6 o'clock
 - 3). Display mode: STN/Negative/Transmissive/Blue
 - 4). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
 - 5). IC: SBN0064G / SBN6400G
 - 6). Backlight: Edge White
 - 7). Dimensions with mark "*" are important, with mark "(") are referenced
 - 8). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	/CS1	/RST	/CS2	/CS3	Vout	BLA	BLK

REV	REVISION RECORD	DATE
A0	First issue	1-5/11



深圳市三元晶科技有限公司
 ShenZhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO.	SYB19264C1V11-3C9BLN7R	GENERAL TOL: ± 0.3
APPROVED BY	CHECKED BY	DRAWING BY
		Jequil
PAGE?	1 OF 1	UNIT: mm
PROJECTION		