



Pin	J1
1	VSS
2	VDD
3	NC
4	/WR
5	/RD
6	/CS
7	RS
8	/RST
9	DB0
10	DB1
11	DB2
12	DB3
13	DB4
14	DB5
15	DB6
16	DB7
17	DB8
18	DB9
19	DB10
20	DB11
21	DB12
22	DB13
23	DB14
24	DB15
25	BLK
27	TP_MBO
28	TP_M7
29	TP_M04
30	TP_BUSY
31	TP_SCK
32	TP_CS

## Specification:

- 1). Driving:VDD:5.0V
- 2). Viewing direction: 12 o'clock
- 3). Display mode: TFT 320\*240 65K Colour
- 4). Operating temp.: -20°C~+70°C
- 5). Storage temp.: -30°C~+80°C
- 6). Control IC: SSD1963
- 7). Backlight :VBL:5.0V
- 8). All the raw materials are RoHS compliant
- 8). Interface:8Bit 16Bit 8080/6800;SPI;I2C;RS232

REV	REVISION RECORD	DATE	 <b>深圳市三元晶科技有限公司</b> ShenZhen TCCLCD HI- Tech Co., Ltd.		
A	FIRST ISSUE	2016/04/22			
B			MODEL NO. 模组型号	SYC320240A035V21-5C40ALN68-85NC	GENERAL TOL: 未注公差 ±0.3
C			APPROVED BY 审核	CHECKED BY 检查	DRAWING BY 绘图
D			Liu 2016/04/22	Francis 2016/04/22	Luoxian 2016/04/22
			PAGE: 页面1 OF 1	UNIT: 单位:mm	PROJECTION 三角法